


PBH | Plastic Ball Knobs

With Tapped Insert or Molded-in Threads • Inch Size



RoHS Compliant

Ball knob

Black phenolic plastic, glossy finish

Tapped insert

Brass, molded-in

Plain Thread

Molded-in

Plastic ball knobs can be used on machine tools, jigs, fixtures, and a variety of other equipment.

For certain minimum quantities, other colors are available upon request.


Maximum heat resistance of phenolic plastic:
150°C (300°F).

Tapped Insert Type

Dimensions in: inches (millimeters)

Part Number	A	D Tapped	Thread Depth	B	C
L02-6771	.75 (19.1)	6-32	.31	.70 (17.8)	.38 (9.7)
L02-6772		8-32	.31		
L02-6773		10-24	.31		
L02-0025		10-32	.31		
L02-0028		1/4-20	.38		
L02-0031	1 (25.4)	10-32	.31	.97 (24.6)	.50 (12.7)
L02-0034		1/4-20	.44		
L02-0037		1/4-28	.44		
L02-0040		5/16-18	.44		
L02-0043		5/16-24	.44		
L02-0046		3/8-16	.50		
L02-0049	3/8-24	.50			
L02-0052	1.19 (30.2)	1/4-20	.44	1.13 (28.7)	.56 (14.2)
L02-0055		5/16-18	.44		
L02-0058		5/16-24	.44		
L02-0061		3/8-16	.50		
L02-0064		3/8-24	.50		
L02-0067	1.38 (35.1)	1/4-20	.44	1.30 (33.1)	.63 (16)
L02-0070		5/16-18	.44		
L02-0073		5/16-24	.44		
L02-0076		3/8-16	.50		
L02-0079		3/8-24	.50		
L02-0082		7/16-20	.50		
L02-0085		1/2-13	.63		
L02-0088		1/2-20	.63		
L02-0094	1.50 (38.1)	5/16-18	.63	1.52 (38.6)	.64 (16.3)
L02-0097		3/8-16	.63		

Table continued...



Dimensions in: inches (millimeters)

4

Revolving and Operating Handles

Part Number	A	D Tapped	Thread Depth	B	C
L02-0103	1.63 (41.4)	5/16-18	.44	1.58 (40.1)	.69 (17.5)
L02-0106		5/16-24	.44		
L02-0109		3/8-16	.50		
L02-0112		3/8-24	.50		
L02-0115		7/16-20	.50		
L02-0118		1/2-13	.63		
L02-0121		1/2-20	.63		
L02-0130	1.88 (47.8)	3/8-16	.50	1.80 (45.7)	.75 (19.1)
L02-0133		3/8-24	.50		
L02-0136		1/2-13	.63		
L02-0139		1/2-20	.63		

Molded-in Thread

Dimensions in: inches (millimeters)

Part Number	A	D Thread	Thread Depth	B	C
L02-0091	1.50 (38.1)	1/4-20	1	1.23 (31.2)	.63 (16.0)
L02-0100	1.5 (38.1)	1/2-13	1.13	1.23 (31.2)	.63 (16.0)
L02-0124	1.88 (47.8)	3/8-16	.63	1.80 (45.7)	.75 (19.1)
L02-0127		3/8-24	.63		
L02-0142		5/8-18	.88		