

## MOBILE HYDRAULIC PULLER

BETEX HXPM 50 - 2/3 arm puller, **self-centering**  
50 ton capacity



# 50 TONS

**For dismounting of all kinds of transmission parts such as bearings, couplings, gears, wheels etc.**

- **Practical**  
The puller is self-centering, easy to maneuver and adjustable in height. Easy to convert to 2-arm or 3-arm puller. The arms slide inwards or outwards simultaneously.
- **Fast**  
The complete stroke is 330 mm. Four adapters (extensions) are included with a maximum length of 620 mm.
- **Strong**  
The harder the force, the tighter the jaws grip. The arms cannot bend or deflect.
- **Safe**  
The integral safety release valve prevents overloading and ensures that you will never exceed the maximum power capacity.

### Advantages

- Prevents damage to shaft and object being pulled
- One person can do the job
- Efficient and saves time
- Including 4 adapters
- Including remote control
- Including safety blanket

Detail electric-hydraulic pump



## MOBILE HYDRAULIC PULLER

BETEX 50 HXPM - 2/3 arm puller, **self-centering**  
50 ton capacity



1. Height adjustment: footpump
2. Double-acting handpump for holding, opening and closing the jaws for safe, secure grip on job
3. Electro-hydraulic pump, 230V - 700 bar, operates the cylinder.  
This is a 4-stage pump with oil delivery 4.2 liters/minute at 0 bar pressure.
4. Self-centering; The arms slide inwards or outwards simultaneously.
5. The design prevents the puller jaws from slipping or deflecting
6. Puller can easily be converted from 3- to 2-arm configuration
7. The puller is adjustable 5° vertically
8. The cart has two swivel castors (self-locking) and has two rigid castors
9. The hydraulic cylinder is a 2-stage spring-return type with a max. working pressure of 700 bar (50 ton)
10. Four adapters (extensions) with a total length of 620 mm are included

Type / art. no.	HXPM 50 t / long / 700014	HXPM 50 t / short / 700017
Capacity in tons	50	50
Max. stroke in mm	330	330
Max. spread in mm	1250	950
Min. spread in mm	75	75
Max. shaft length in mm	720	500
Operating main cylinder	electro-hydraulic pump, 230V - 16A, with remote control	
Operating height adjustment	foot pump	
Operating self-centering jaws	hand pump, double acting	
Adapters 4 items in mm	2 x Ø 40, 2x Ø 50: length 155	
Min. height (from the centre) in mm	820	820
Max. height (from the centre) in mm	1370	1370
Manometer	700 bar	700 bar
Weight in kg	372	342





# GRUPO PEGAMO DESDE 1982



## SUMINISTRO INDUSTRIAL

En Pegamo Suministro Industrial llevamos desde 1982 vendiendo, alquilando y reparando Herramienta Hidráulica, Herramienta Neumática y Herramienta Manual de las principales marcas del mercado.

Te asesoramos para que encuentres la mejor solución a las necesidades de tu empresa.

### CONTACTA CON NOSOTROS

Pol. Lintzirin Gaina, B2  
20180 Oiartzun.  
Gipuzkoa - Spain

[suministros@pegamo.es](mailto:suministros@pegamo.es)  
T. 943 491 788  
F. 943 371 001