



ISO 9001 Supplier

RoHS Compliant



GN 323.4 | Aluminum Safety Clutch Handwheels

With Friction Bearing Mechanism •
Metric Size • Solid Disk

Body	Aluminum, black powder coated pebble finish
Clutch	GN 000.4 series, page 249
Diameter d₁	4.92 – 9.84 inch (125 – 250 mm)
Diameter d₂	.472 – .866 inch (12 – 22 mm)
Types	Engage by Pulling or Pushing




Engage by pulling



Engage by pushing

Washer GN 184



ISO 9001 Supplier

RoHS Compliant



GN 323.5 | Aluminum Safety Clutch Handwheels

With Needle Bearing Mechanism •
Metric Size • Solid Disk

Body	Aluminum, black powder coated pebble finish
Clutch	GN 000.5 series, page 250
Diameter d₁	4.92 – 9.84 inch (125 – 250 mm)
Diameter d₂	.472 – .866 inch (12 – 22 mm)
Types	Engage by Pulling or Pushing




Engage by pulling



Engage by pushing

Washer GN 184



ISO 9001 Supplier

RoHS Compliant



GN 322.4 | Aluminum Safety Clutch Handwheels

With Friction Bearing Mechanism •
Metric Size • Two Spoked

Body	Aluminum, see GN 322 series
Clutch	GN 000.4 series, page 249
Diameter d₁	4.92 – 9.84 inch (125 – 250 mm)
Diameter d₂	.472 – .866 inch (12 – 22 mm)
Types	Engage by Pulling or Pushing




Engage by pulling



Engage by pushing

Washer GN 184



ISO 9001 Supplier

RoHS Compliant



GN 322.5 | Aluminum Safety Clutch Handwheels

With Needle Bearing Mechanism •
Metric Size • Two Spoked

Body	Aluminum, see GN 322 series
Clutch	GN 000.5 series, page 250
Diameter d₁	4.92 – 9.84 inch (125 – 250 mm)
Diameter d₂	.472 – .866 inch (12 – 22 mm)
Types	Engage by Pulling or Pushing



Engage by pulling



Engage by pushing

Washer GN 184

