





**GN 322.7 | Aluminum Two-Spoked Handwheels**



With Safety Retractable Handle •  
Inch and Metric Size



<b>Body</b>	Aluminum, gravity die-cast
<b>Rim</b>	Turned and highly polished
<b>Retractable Handle</b>	Plastic, black oxide steel retracting mechanism
<b>Diameter d<sub>1</sub></b>	4.92 – 9.84 inch (125 – 250 mm)
<b>Diameter d<sub>2</sub></b>	.500 – .750 inch or 10 – 22 mm



ISO 9001 Supplier





**EN 622 | Plastic Ergostyle® Two-Spoked Handwheels**



With or without Revolving Handle •  
Inch and Metric Size



<b>Body</b>	Technopolymer plastic, black
<b>Hub</b>	Steel, black oxide finish
<b>Revolving Handle</b>	Plastic, zinc-plated steel spindle
<b>Diameter d<sub>1</sub></b>	4.88 – 7.87 inch (124 – 200 mm)
<b>Diameter d<sub>2</sub></b>	.375 – .625 inch or 12 – 20 mm



5

Handwheels

ISO 9001 Supplier

Call for RoHS

Elesa Model ETW+I





**EN 622.3 | Plastic Ergostyle® Two-Spoked Handwheels**



With Retractable Handle • Inch and Metric Size



<b>Body</b>	Technopolymer plastic, black
<b>Hub</b>	Steel, black oxide finish
<b>Retracting Mechanism</b>	Plastic, black oxide steel stem
<b>Diameter d<sub>1</sub></b>	4.92 – 7.87 inch (125 – 200 mm)
<b>Diameter d<sub>2</sub></b>	.375 – .625 inch or 12 – 20 mm



Elesa Model ETW+IR

ISO 9001 Supplier

Call for RoHS





**DIN 950-CI | Cast Iron Spoked Handwheels**



With or without Revolving Handle



<b>Body</b>	Cast iron, gravity die-cast
<b>Rim</b>	Turned and polished
<b>Revolving Handle</b>	Steel, zinc-plated
<b>Diameter d<sub>1</sub></b>	3.15 – 19.69 inch (80 – 500 mm)
<b>Diameter d<sub>2</sub></b>	.500 – .875 inch (10 – 34 mm)



ISO 9001 Supplier

RoHS Compliant