



GN 609.5 | Stainless Steel Spacer Bushings

Metric Size • For Indexing Plungers



ISO 9001 Supplier

RoHS Compliant

Bushing

Stainless steel, European Standard No. 1.4305 (American Standard 303)

GN 609.5 spacer bushings compensate for the body thread lengths on indexing plungers to allow mounting through walls of varying thicknesses.

Bushings are suitable for use with these indexing plungers: GN 607, page 537, GN 607.1, page 539, GN 617, page 521, GN 617.1, page 529, GN 717, page 547, GN 817, page 532, and GN 822, page 843.

Metric Table

Dimensions in: millimeters (*inches*)

Part Number	d ₁ H ₁₂	d ₂ -.01 mm	l Length ±.1	Fits Thread Sizes for Indexing Plungers											
				GN 607 GN 607.1	GN 617 GN 617.1	GN 717	GN 817	GN 822							
10W2LGA	8 (.31)	10 (.39)	2	-	-	M8 x 1.25	M8 x 1.0 or (5/16-18)	M8 x .75							
10W3LGA			3												
10W4LGA			4												
10W6LGA			6												
10W8LGA			8												
10W10LGA			10												
12W2LGB	10 (.39)	12 (.47)	2	-	M10 x 1.0 or (3/8-24)	M10 x 1.5	M10 x 1.0 or (3/8-16)	M10 x 1.0							
12W4LGB			4												
12W6LGB			6												
12W8LGB			8												
12W10LGB			10												
12W12LGB			12												
14W2LGC	12 (.47)	14 (.55)	2	-	M12 x 1.5 or (1/2-13)	M12 x 1.75	M12 x 1.5 or (1/2-13)	-							
14W4LGC			4												
14W6LGC			6												
14W8LGC			8												
17W2LGC			12 (.47)						17 (.67)	2	M12 x 1.5	-	-	-	-
17W4LGC										4					
17W5LGC	5														
17W4LGD	4														
17W6LGD	6														
17W8LGD	8														
17W10LGD	16 (.63)	17 (.67)	10	-	-	-	M16 x 1.5 or (5/8-11)	-							
17W12LGD			12												
19W2LGD			16 (.63)						19 (.75)	2	M16 x 1.5	M16 x 1.5 or (5/8-11)	-	-	-
19W4LGD										4					
19W6LGD										6					
19W8LGD										8					
19W10LGD	10														
19W12LGD	12														

10

Indexing, Spring and Ball Plungers