



EN 603 | Ergostyle® Plastic Adjustable Levers

Push Button • Threaded Stud Type • Inch Size



ISO 9001 Supplier

RoHS Compliant

Body and toothed element

Special glass-fiber reinforced technopolymer, black matte finish

Stud

Zinc-plated steel with chamfered end

Spring

AISI 302 stainless steel

Push button: "C2" = standard orange
RAL 2004 matte finish technopolymer.

Optional colors

- C1** Black RAL 7021
- C3** Gray RAL 7035
- C4** Yellow RAL 1021
- C5** Light Blue RAL 5024
- C6** Red RAL 3000

Elesa® original design plastic adjustable lever. The slightly arched ergonomic shape of the handle gives the operator a comfortable and safe grip, while the thumb rests naturally on the push button.

Particularly suitable when lever turning angle is limited owing to a lack of space.

Pulling the lever upward disengages the serrations, allowing it to be swiveled to the ideal clamping position. On releasing the lever, the serrations automatically re-engage.

Resistant to solvents, oils, grease and other chemical agents.

Heat resistance to 130°C (265°F).

Elesa Model ERX.p

Inch Table

Dimensions in: inches (millimeters)

Part Number*	l_1	d_1 Thread	l_2 Stud Length	d_3	h_3	h_1	h_2	d_2	h_4
2T75CD0K/C2	1.73 (44)	10-24	.75	.61 (15.5)	1.28 (32.5)	1.16 (29.5)	.24 (6)	.47 (12)	.14 (3.5)
1T5000CD0K/C2		10-32	.50						
1T75CD0K/C2			.75						
3T75CD0K/C2		1/4-20	.75						
3T1CD0K/C2			1.00						
5T75CD1K/C2	.75								
5T1CD1K/C2	2.48 (63)	5/16-18	1.00	.75 (19)	1.69 (43)	1.48 (37.5)	.31 (8)	.59 (15)	.16 (4)
5T126CD1K/C2			1.25						
6T1CD2K/C2			1.00						
6T126CD2K/C2	3.07 (78)	3/8-16	1.25	.91 (23)	2.13 (54)	1.85 (47)	.47 (12)	.75 (19)	.16 (4)
6T1500CD2K/C2			1.50						

* For optional-standard colors replace the last digit with the desired suffix: **C1** (Black RAL 7021), **C2** (Orange RAL 2004), **C3** (Gray RAL 7035), **C4** (Yellow RAL 1021), **C5** (Light Blue RAL 5024), **C6** (Red RAL 3000). Example of part number for Orange RAL 2004 lever: 2T75CD0K/C2